

CuSn10

Copper-tin alloy with high elongation and medium hardness suits for a wide range of industrial applications

Key Features:

- > Excellent mechanical properties
- > Good corrosion resistance
- > Good electrical and thermal conductivity
- > Resistance to cavitation in sea water

Example Applications:

- > Parts and housings for maritime applications
- > Heat exchangers, rocket engine parts, induction coils, electronics
- > Versatile applications requiring good conductivity

[Technical Data]

Part Density ISO3369	≥8.80 g/cm³
Tensile Strength ISO6892-1	n/a
Yield Strength ISO6892-1	n/a
Elongation after Fracture ISO6892-1	n/a
Vickers hardness ISO6507-1 / ISO6508-1	n/a
	Tensile Strength ISO6892-1 Yield Strength ISO6892-1 Elongation after Fracture ISO6892-1

¹ For more information on heat treatment process, please contact us directly.

Farsoon systems are open material platform. For special materials such as tungsten, tantalum and pure copper, please contact us with your inquiries or requirements.

Disclaimer: Many factors may affect the performance characteristics of products. We recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. Farsoon makes no warranties of any type, express or implied, including but not limited to, the warranties of merchantability or fitness for a particular use. This also applies regarding the consideration of possible intellectual property rights as well as laws and regulations. Farsoon reserves the right to change the technical data without notice. Farsoon*, Buildstar*, Makestar* are registered trademarks of Farsoon Technologies. Last Change: 2024-09



Aerospace Air Cooled Camera Housing System: FS121M

www.farsoon.com